

FOGGING MACHINE

FOGGERS[®]
INDIA
PVT. LTD.

MODEL 1200



1

MODEL 1200

- * 454 liters/hr. Enables you to fog 3 times faster than conventional vehicle mounted foggers.
- * Tremendous capacity is capable of covering 12 acres in one minute (49,000 sq. meters/minute).
- * Powered by a high quality 9 H.P. overhead valve, Briggs & Stratton engine.
- * 20 Ft. remote cable with locking connector.
- * Adjustable fog output - dry to wet fog 57-454 liters/hr.
- * Oil heat - known and proven technology.
- * Use kerosene, diesel fuel for complete fogging operation.
- * Completely remote controlled starting fogging stopping.
- * Saves Man - hours - truck time - faster coverage.
- * Highest quality of components and operating mechanism - no special tools required insecticide system easily cleaned without use of tools.
- * Instant reading (a) Hour meter (b) Temperature meter
- * Absolutely no containers under pressure - no dangerous L.P., gas no formulation drum pressure.
- * Two 120 volt AC receptacles mounted on machine.

MODEL 1200 SPECIFICATIONS

Insecticide Output	57-454 Liter/Hr.
Weight (Empty)	211.8 Kg
Weight (Full)	281 Kg.
Length (w/Nozzle)	199 cm.
Length (w/o Nozzle)	139 cm.
Width	13.8 cm
Height	12.6 cm.
Gasoline Engine	9 Hp.Overhead valve
Tank capacity	4.76 Liters
Heater Tank	
Capacity	56.8 Liters (5 Hrs.)
Fog Particle Size	10- 100 Microns
Sghipping Data:	
L x W X H	152 x 109 x 107 (cm)
Weight	265.36 Kg.